J/109 Specifications

Hull & Deck

- Lloyd's approved, CK-57AL-600 Baltek Contourkore end grained balsa composite construction using biaxial and unidirectional glass fabrics with vinylester resin on outer hull layer.
- Patented SCRIMP® resin infusion system molding process for optimum laminate strength with 65-70% glass content in structural skins.
- Pearson Composites 10 year transferable warranty against hull blistering.
- 3,900 lb. 7.0' draft, variable chord, high lift, lead keel bolted and epoxy bonded to deep molded stub w/sump. (4,260 lb. 5.75' shoal keel optional)
- · Off-white deck with a high traction molded non-skid.
- . Contrasting color double boot stripe on hull.
- . Low maintenance molded ORC size foredeck toe-rails.
- . Bow locker with deck hatch for anchoring gear.
- . Molded cockpit storage & LPG Gas lockers
- · Molded stern platform w/swim ladder mount.
- Molded companionway instrument pod with spray shield dodger storage.
- . GRP molded structural primary bulkhead.
- . SCRIMP molded structural grid.
- SCRIMP molded heavy-duty ring frame accepting shroud loads through stainless tie rods.
- All intermediate bulkheads glassed to hull and deck for additional stiffness.
- · Custom aluminum mast step included within grid.

Propulsion & Steering

- Yanmar 3YM30C 29 hp. diesel engine with saildrive, hour meter, 100 amp Balmar alternator, and fresh watercooling with heat exchanger.
- Yanmar lighted panel recessed in cockpit includes electric stop, tachometer, alarms for oil, battery, and temperature.
- · Fuel gauge in cockpit.
- . Engine throttle control.
- 1" Engine insulation with removable front and side engine cover access hatches.
- 20-gallon fuel capacity with baffles and inspection/clean out located under aft cabin berth.
- 2 bladed Flex-O-Fold geared folding propeller.
- High aspect balanced rudder design w/large diameter custom molded FRP shaft mounted in Edson rudder bearings to exceed ABS specs.
- Edson 54" Diamond Series aluminum wheel with natural leather grip on custom molded pedestal with 5" Ritchie compass, through shaft brake, and wheel height stainless guard.
- Custom designed aluminum emergency tiller.

Plumbing & Electrical

- · Manual bilge pump in cockpit.
- . Electric bilge pump w/switch & vented loop.
- · Manual fresh water foot pump in head and galley.
- 35-gallon water tank under port settee (additional water optional).

- Raritan Marine head with holding tank and "Y" valve and overboard discharge pump.
- . Icebox drain with valve.
- . Direct overboard head/shower sump pump.
- . Cold pressure water system (Hot water option).
- Marelon seacocks and double-clamped hoses below the waterline.
- DC Lighting package to include swiveling tulip & dome lights with fluorescent light in head.
- (2) 105amp deep cycle AGM glass-mat batteries.
- 12V Hella DC metered distribution panel with Hella DC battery monitoring system.
- . Battery switch with DC main breaker.
- . DC outlet plug in nav station
- UL approved stranded, tinned copper ABYC color-coded wiring throughout.
- · Navigation lights and steaming light.
- . Seahood with 6 wire 22 gauge cable to nav station.
- . Bonding system to meet ABYC project E-1.

Deck Hardware

- (2) Harken 46.2 AST (self-tailing) primary winches.
- . (2) Harken 40.2 AST secondary winches.
- (2) 10" Harken Speed-Grip aluminum lock-in winch handles w/(2) PVC handle holders.
- 6:1 Harken mainsheet system with integral 4:1 fine tune.
- · Harken 4:1 traveler system.
- · Harken Adjustable Jib/Genoa lead system with purchase.
- Harken Black Magic 57mm 1967 foot blocks on cockpit coaming side for genoa sheets.
- (4) Folding Wichard pad eyes for outboard genoa & jib leads mounted outboard of standard tracks. (2 ea side)
- 150 cams for lazy spin sheets when not in use.
- (3) Harken 1958 for tack line on bowsprit and spinnaker sheet blocks on U-bolts fwd of stern pulpit legs to P&S.
- (8) Harken 6050 teardrop halyard/reef turning blocks mounted to aluminum mast collar. Halyards lead aft through (2) Harken quad 6066 organizers to Spinlock XTS double stoppers.
- Roller furling control line w/Harken 2636 foredeck block, S.S. lined bulleye fairleads and Harken 150 cam cleat w/425 cam fairlead.
- 2:1 J/Sprit control line leading to (2) Harken 0350 Sprit blocks, 340 block on forward bulkhead, aft through bulkheads and starboard handrail to cockpit 150 cam.
- (2) Bow chocks, (2) 8" bow cleats, (2) 8" stern cleats.
- Custom S.S. stemplate strap w/ U-Bolt tack fitting, chainplates, & backstay tang. (optional anchor roller).
- . (2) Skylight Hatches of sizes 15" x 20" and 22" x 22".
- Five aluminum framed cabin opening ports (two of 12" & three of 24" lengths), one fixed 24" port above nav station, on cabin sides. Three 12" cockpit opening ports.
- Thurston cockpit dodger with side curtains mounted against splash molding (choice of standard Sunbrella colors).
- Acrylic companionway drop board with nylon storage rails in cockpit locker.

J/109 Specifications Continued

- ORC Size double 5/32" lifelines & tapered stainless stanchions w/ bases, large gates to port and starboard, custom bow & stern rails, and stern gate.
- Telescoping stern swim/boarding ladder.
- . (4) 12" x 24" poly mesh line bags.
- Flag staff and 3 x 5 American flag.
- . Two helmsman footrests in teak.

Gallev

- Gimbaled, 3 burner (including oven), Force 10 LPG stove/oven w/S.S. safety bar.
- Highly polished double stainless sink mounted to wheat colored laminate counter top.
- Molded icebox with foam insulation, single lid, and utility storage shelves.
- (2) Dry goods storage areas w/ shelf & acrylic slider covers.
- . Two utensil drawers aft of stove.
- . Additional storage cabinet below drawers.
- Laminated wood fiddle with integral handhold around sink island.
- Pot and pan storage in cabinet under stove/oven.
- . Trash storage under sink w/flip lid access.
- Cabinet for cleaning supplies and to access trash under sink.

Spars & Rigging

- Double spreader Sparcraft One-Design anodized aluminum mast & boom package with white powder coat finish.
- Sparcraft Performance Vang with purchase system.
- Retractable Carbon Fiber J/Sprit extendable to 5.5' beyond bow w/integral end caps and adjuster system.
- Continuous rod rigging package with Hall pre-assembled headstay for standard Harken headsail furling.
- Hall running rigging package including Technora main & genoa halyards, Spectra spin halyard and sheets, XLS polyester main & jib sheets, and control lines.
- Harken split-drum Unit 1.0 standard headsail furling system.
- · Sailtec -8 integral hydraulic backstay adjuster.

Interior

- · Varnished cherry wood interior.
- Varnished cherry hull siding in main cabin. Vinyl lined hull siding in cabins forward and aft (varnished wood hull siding optional in these cabins).
- . Simulated ½" teak & holly cabin sole.
- Forward cabin includes 2 hanging lockers with locker doors and shelves above, hinged access to storage below berth, and full-length shelf over V-berth to port.
- Aft cabin to port with recessed door to main cabin, hanging locker with door and shelf above and large berth with full-length shelf on hull.
- Settee berths in main cabin with shelves outboard, and storage behind back rests (tanks and storage under).

Deluxe bolstered cushions w/choice of nylon fabric colors in main salon, nav station and cabins.

- Drop-leaf table with wood fiddles & bottle storage compartment.
- Chart table w/chart storage under table, shelf storage outboard, hinged overhead electrical & instrumentation panel. Tool storage below hinge-up seat, single drawer with cabinet on inboard face below table, and open compartment outboard under tabletop.
- Head with recessed wood trimmed door from main cabin and access door to starboard aft cockpit locker. Head includes handheld shower, sink, vanity, mirror, handhold and storage.
- · Angled teak companionway treads with non-skid strips.
- · Vinyl overhead in main, forward, aft cabins and head.

Package Options

Comfort Group

 Includes three piece cockpit cushion set for helmsman coordinated canvas work of lifeline pads and mainsail cover with J/109 emblem to match dodger.

Systems Group:

 Includes: Hot water tank and plumbing, cockpit shower, plus additional 35 gal water tank.

DC Refrigeration:

 12V Seafrost DC Refrigeration System and Additional 3rd 105amp Deep Cycle glass mat battery.

Marina Group:

 Includes 120VAC/30A shore power service with Pro Mariner battery charger, 50ft cord, AC panel, and five GFI protected outlets.

Deluxe Trim Group:

 Includes varnished wood ceilings in the forward and aft cabins.

Other Options

- . Two Tone Deck
- . Cove Stripe
- . 5.75' 4,260 lb. Shoal Draft Keel.
- Removable transom locker/dock box (Molded in same color as deck).
- Varnished Louvered Storage Cabinets in Main Cabin (port and/or starboard).
- . Removable Bow Anchor Roller.
- Removable varnished teak cockpit table w/storage bag

Notice

Specifications are effective as of hull #312 and subject to change without prior notice or obligation. J/109s will be constructed with specifications in effect at time of construction. J Boats reserves the right to periodically upgrade these specifications through additions, deletions and substitutions.